



KC-505

HEAVY-DUTY HIGH FOAMING CAUSTIC CLEANER



DANGER

Causes severe skin burns and eye damage. Prevention: Do not breathe dusts or mists. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. **Response:** Immediately call a poison center or doctor. Specific treatment (see Section 4 on SDS). **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or

doctor. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing and shoes before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. **IF SWALLOWED:** Rinse mouth. DO NOT induce vomiting.

Storage: Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Additional Precautions: Corrosive! Contains sodium and potassium hydroxide.

Read SDS before using this product.

DIRECTIONS FOR USE: KC-505 is normally diluted at the rate of 2-12 ounces per gallon of water depending upon soil to be removed, the temperature of the cleaning bath and the time allowed for cleaning. When used in pressure washing, the typical dilution is 50-100:1. KC-505 may be used in all departments of meat, poultry and general food processing plants.

Note: This product is not safe on soft metals, galvanized and painted surfaces.

SAMPLE



PSSI Chemical Innovations
3729 Peddle Hollow Rd.
Kieler, WI 53812 USA
888-671-5366

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PPE	D



NET CONTENTS: 5 GALLONS ___
55 GALLONS ___
275 GALLONS ___

BATCH:

FOR INDUSTRIAL USE ONLY
NOT FOR RETAIL SALE

ID #20076

CHEMTREC EMERGENCY PHONE 1-800-424-9300

UN1760

, Corrosive liquid, n.o.s., 8, PG II
(contains sodium and potassium hydroxides)