



OXYCIP

BLEACHING COMPOUND



DANGER

Causes severe skin burns and eye damage. May cause fire or explosion; strong oxidizer. Prevention: Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep/Store away from clothing/

combustible materials. Take any precaution to avoid mixing with combustibles. Wear fire/flammable resistant/retardant clothing. **Response:** Immediately call a poison center or doctor. Specific treatment (see Section 4 on SDS). **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. **IF ON CLOTHING:** Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. **In case of major fire and large quantities:** Evacuate area. Fight fire remotely due to the risk of explosion. **In case of fire:** Use Water spray, fog or regular foam for extinction.

Storage: Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant

Read SDS before using this product.

DIRECTIONS FOR USE: Use approximately 6 to 12 oz. of Oxycip per 1 gallon of water for bleaching of plastic belts, tubs, and utensils. For more information, please contact your PSSI Chemical Innovations' Representative.

Additional Precautions: OXIDIZER! Contact with combustibles may cause fire. Decomposes yielding oxygen that supports combustion of organic matter and can cause overpressure if confined. Store in cool area out of direct sunlight and away from combustibles. Containers must be vented. Avoid contact with reducing agents, wood, paper, heavy metals, caustic. Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all residue is removed. Never return unused Oxycip to the original container. Avoid contact with eyes, skin, and clothing. Avoid breathing mists. Use proper personal protective equipment when handling.

HEALTH	3
FLAMMABILITY	0
REACTIVITY	1
PPE	H



NET CONTENTS: 4.7 GALLONS ____
52 GALLONS ____
250 GALLONS ____
330 GALLONS ____



PSSI Chemical Innovations
3729 Peddle Hollow Rd.
Kieler, WI 53812 USA
888-671-5366

CHEMTREC EMERGENCY PHONE 1-800-424-9300

BATCH:

FOR INDUSTRIAL USE ONLY
NOT FOR RETAIL SALE

ID #20586

UN2014

, Hydrogen Peroxide, aqueous solutions with 34% hydrogen peroxide 5.1 (8), PG II