

## TECHNICAL DATA

### TROLLEX LQ

#### Description:

Trollex LQ is a powerful blend of caustic and surface active agents. Trollex LQ is designed to be used as a heavy-duty trolley cleaner and features outstanding performance on hard surfaces to remove soils and oil build-ups. It adheres to and cleans vertical surfaces.

#### Physical Properties:

Appearance - Clear brown liquid  
Odor - Mild  
pH, 2% solution - >13  
Density - 12.14 pounds per gallon  
Foaming - Low/Medium  
Rinsing - Excellent

#### Directions for Use:

Use in any cleaning apparatus. Dilute 2-14 ounces of Trollex LQ per gallon of hot water (110-170°F). Dilution rate depends upon soil to be removed, water temperature and time allowed for cleaning. Apply to surfaces such as stainless steel, black iron, and mild steel. After use rinse thoroughly with potable water to remove all residue. Do not use on aluminum or other soft metals. When in doubt, pretest on small areas.

Before use in federally inspected meat and poultry food processing plants and dairies, food products and packaging materials must be removed from room or carefully protected.

#### Safety:

Danger! Corrosive. Contains sodium and potassium hydroxides. Causes severe skin burns and eye damage. Avoid contact with eyes, skin and clothing. In case of skin contact, flush skin with water. In case of eye contact, flush eyes with water for at least 15 minutes and call a physician.

Read Safety Data Sheet (SDS) before using this product.

#### Storage:

Keep container closed and store in a cool, dry place.