

TECHNICAL DATA

KC-266

Description:

KC-266 is an alkaline powdered cleaner for use in high pressure spray washers or soaking of aluminum and light metal materials. It is inhibited for use on soft metals as well as steel. It offers high detergency power, moderately low alkalinity and free rapid rinsing action. It eliminates water spotting due to hard water, emulsifies grease and oil, and rinses rapidly and completely.

Physical Properties:

Appearance - White granules

Odor - Mild alkaline

pH, 2% solution - 11.5-13.5

Foaming - Low

Rinsing - Excellent

Directions for Use:

Use 2 to 4 ounces per gallon at 150°F to 180°F for pressure spray method. For manual application, use 3 to 8 ounces of KC-266 per gallon of water at temperature of 100°F to 150°F. For tough soils use a solution of up to 2 pounds KC-266 per gallon of water. Rinse thoroughly with potable water to remove all residue.

Before use in federally inspected meat and poultry food processing plants and dairies, food products and packaging materials must be removed from room or carefully protected.

Safety:

Moderately high alkaline. It will not harm tin, aluminum, copper, brass, galvanized or steel. Avoid contact with skin and eyes. In case of skin contact, flush with plenty of water and clean with mild soap. In case of eye contact, flush with plenty of water for 15 minutes and get medical attention. Harmful if inhaled, use with adequate ventilation.

Read Safety Data Sheet (SDS) before using this product.

Storage:

Keep container closed and store in a cool, dry place.