



KC-560

POWDERED FLOOR CLEANER



DANGER

Harmful if swallowed. Causes severe skin burns and eye damage. May cause respiratory irritation. Prevention: Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dusts or mists. Wear protective gloves/protective clothing/eye

protection/face protection. Use only outdoors or in a well-ventilated area. **Response:** Immediately call a poison center or doctor. Specific treatment (see Section 4 on SDS). **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. **IF SWALLOWED:** Call a poison center or doctor if you feel unwell. Rinse mouth. DO NOT induce vomiting.

Storage: Store locked up.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Additional Precautions: Corrosive! Contains sodium percarbonate.

Read SDS before using this product.

HEALTH	2
FLAMMABILITY	0
REACTIVITY	0
PPE	B



NET CONTENTS: 40 POUNDS _____
450 POUNDS _____

BATCH:

FOR INDUSTRIAL USE ONLY
NOT FOR RETAIL SALE ID #20080

KC-560 is a powdered alkaline cleaner with an oxygen generating additive for use in utensil, equipment, and floor cleaning in food processing operations. KC-560 provides intensive cleaning by removing difficult stains and lifting soils.

DIRECTIONS FOR USE: Floor Cleaning: Remove gross soils from floor surfaces. Apply KC-560 at a rate of 2-3 pounds of product per 1,000 sq. ft. of surface area. Rinse area thoroughly with potable water to remove all product residue. It may not be applied to the floor during production as an anti-slip additive and must be thoroughly rinsed off prior to start up.

Utensils and Equipment Cleaning: Prepare a solution of 2-10 ounces of KC-560 per gallon hot water (120°F-140°F), depending on the soil level. Apply by soaking, spraying, or mopping. Let dwell for 15-20 minutes. Do not allow the chemical to dry on the surface. Brush or scrub if needed. Rinse thoroughly with potable water to remove all residue.

KC-560 is not a replacement for hard surface sanitizing/disinfecting.



PSSI Chemical Innovations
3729 Peddle Hollow Rd.
Kielers, WI 53812 USA
888-671-5366

CHEMTREC EMERGENCY PHONE 1-800-424-9300

UN1759

, Corrosive solids, n.o.s., 8, PG III
(Contains sodium trioxosilicate)