

FB-1559







DANGER

Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage. Suspected of causing cancer.
Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves/ protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. **Response:** IF exposed or concerned: Get medical advice/attention. Specific treatment (see Section 4 on SDS). **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. **IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. **IF SWALLOWED:** Rinse mouth. Call a poison center or doctor if you feel unwell.

Storage: Store locked up. Store in corrosive resistant container with a resistant inner liner.

Disposal: Dispose of contents/container to an approved waste disposal plant.

Recommended First Aid: IF INHALED: Remove to fresh air. Administer oxygen if breathing is difficult. Call a physician immediately.

Read SDS before using this product.





| _ | | |
|---|--|--|
| | | |
| | | |

| 55 GALLONS | |
|-------------|--|
| 275 GALLONS | |
| 330 GALLONS | |

NET CONTENTS: 5 GALLONS

| ватсн: | |
|--------|--|
|--------|--|

FOR INDUSTRIAL USE ONLY NOT FOR RETAIL SALE

ID #21559

SCALE INHIBITOR

FB-1559 is an additive for use with alkaline cleaning products to reduce filming, prevent and remove mineral scale and build-up. FB-1559 performs well at high temperatures and high pH conditions. It effectively chelates iron and water hardness which cause filming on surfaces. Quickly and effectively removes mineral stone which can harbor bacteria and compromise thermal efficiency of equipment. Phosphate free. FB-1559 may be used on equipment in all departments of dairy, meat, poultry, and general food processing plants.

DIRECTIONS FOR USE: Dilute FB-1559 at 0.1-1.0 oz per gallon of water. Apply through COP or CIP apparatus, as an additive to alkaline wash step. Follow with a potable water rinse to remove all residue.

Before use in federally inspected meat and poultry food processing plants and dairies, food products and packaging materials must be removed from room or carefully protected.

Additional Precautions: Corrosive! Contains ethylenediaminetetraacetic acid tetrasodium salt and sodium hydroxides.



Safe Foods Chemical Innovations

1501 E 8th Street North Little Rock, AR 72114 501-758-8500 888-671-5366

CHEMTREC EMERGENCY PHONE 1-800-424-9300

UN3267, Corrosive liquid, basic, organic, n.o.s., 8, PG III, (contains sodium hydroxide, tetrasodium ethylenediamine tetraacetate)