

TECHNICAL DATA

DRIP GRIP

Description:

Drip Grip will reduce the accumulation of water condensate on overhead surfaces, piping, and other structures, significantly reducing contamination of surfaces with condensate drippage. Drip Grip may be applied to ceilings, overhead piping, and other overhead structures in meat, poultry, dairy, and general food processing plants. Drip Grip is formulated from GRAS ingredients.

Physical Properties:

Appearance – Clear colorless liquid
Odor – Odorless
pH, concentrate – 8
Density – 8.68 pounds per gallon
Foaming – High
Rinsing – Excellent

Directions for Use:

This product can be applied to overhead surfaces with condensation already formed or prior to condensation forming. Dilute 3 ounces of this product per gallon of potable water. Use diluted product at a rate not greater than 1 ounce per 5 square feet (0.2 fl. oz./sq. ft., 1 gallon per 640 sq. ft.). Apply to ceilings, overhead piping, and other overhead structures as a spray. Wait 60 minutes for the solution to drain. Apply Drip Grip to overhead surfaces once every 3 days or as needed.

As with any condensation found in food facilities, overspray from Drip Grip application should be cleaned from food contact surfaces prior to production. In the event of condensate drippage from Drip Grip-treated surfaces, routine condensation removal and decontamination procedures should be employed. Drip Grip does not introduce additional food safety hazards.

Safety:

May cause mild eye irritation. In case of eye contact, flush eyes with water for at least 15 minutes. Wash thoroughly after handling.

Read Safety Data Sheet (SDS) before using this product.

Storage:

Keep container covered and store in a cool, dry place. Keep from freezing.