

## PRECAUTIONARY STATEMENTS

### HAZARDS

**DANGER** May intensify fire, oxidizer. Toxic if swallowed. Toxic in contact with skin. Harmful if inhaled. Causes severe skin burns and eye damage. Very toxic to aquatic life. **Prevention:** Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection, protective gloves and clothing of butyl or "Viton". Avoid release to the environment. Collect spillage. **Response:** Specific treatment (see Section 4 on SDS). Immediately call a poison center or doctor. If skin irritation or rash occurs, get medical advice/attention. **IF IN EYES:** Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. For specific treatment see FIRST AID section below.

### Storage and Disposal

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local regulations.

**Storage:** Store and use in a cool environment, away from alkalis. Never cut, drill, weld or grind on or near this container, whether empty or full. Always replace drum, pail or IBC cap prior to moving the container.

**Disposal:** Do not flush to sewer; may be incinerated in approved facility with flue gas monitoring & scrubbing, mix with a suitable flammable waste before incineration; may be landfilled if local regulations permit. Drums should be reused. Recondition and pressure test by a licensed reconditioner prior to re-use. Pails must be vented and thoroughly dried prior to crushing and recycling. IBCs (intermediate bulk containers): polyethylene bottle must be pressure tested & recertified at 30 months. Replace at 60 months (5 years). Steel containers must be inspected, pressure tested & recertified every 5 years.

### FIRST AID

**GENERAL ADVICE:** Corrosive substance: apply first aid immediately! Inadvertent inhalation of vomited material may seriously damage the lungs. This danger is greater than the risk of poisoning through absorption of this product. Only empty the stomach under medical supervision, after installing an airway to protect the lungs. Directions continued on the right panel.

HEALTH	3
FLAMMABILITY	1
REACTIVITY	1
PPE	X



Rev. 01/10/2024



# PROMOAT RM™

## ANTIMICROBIAL AGENT

Promoat RM™ is a peroxyacetic acid mixture approved by FDA for use in process water or ice used in washing, rinsing, or cooling red meat, carcasses, parts, trim, and organs (FCN No. 2236). Promoat RM™ delivers superior microbial efficacy against a wide range of microorganisms. It kills pathogens through oxidation and greatly extends product shelf-life by immediate and dramatic reduction in food spoilage organisms. Promoat RM™ has shown to cause no organoleptic changes on treated food products.

Before Using This Product, Please Read This Entire Label Carefully.

## KEEP OUT OF REACH OF CHILDREN

# DANGER

## OXIDIZER! CORROSIVE!



## PROTECT FROM HEAT

### NET CONTENTS:

50 GALLONS \_\_\_\_ 300 GALLONS \_\_\_\_

LOT NUMBER:

PRODUCTION

DATE:

**IF IN EYES:** Wash eyes with plenty of water, holding eyelids open. Seek medical assistance promptly if there is irritation.

**IF ON SKIN OR CLOTHING:** Wash with plenty of water. Remove contaminated clothing and do not reuse until thoroughly laundered.

**IF INHALED:** Remove from contaminated area promptly. **CAUTION: Rescuer must not endanger himself!** If victim's breathing stops, administer artificial respiration and seek medical aid promptly.

**IF SWALLOWED:** Give plenty of water to dilute product. Do not induce vomiting. Keep victim quiet. If vomiting occurs, lower victim's head below the hips to prevent inhalation of vomited material. Seek medical help promptly.

## Directions For Use:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### Red Meat:

Promoat RM™ is approved for use in process water or ice used on red meat carcasses, parts, trim, and organs. Usage levels should not exceed: 1800 ppm peroxyacetic acid, 1050 ppm hydrogen peroxide, and 117 ppm HEDP.

## Safe Foods Chemical Innovations

1501 E 8th Street

North Little Rock, AR 72114

501-758-8500



CHEMTREC EMERGENCY PHONE 1-800-424-9300

# UN3109

Organic peroxide type F, Liquid (contains peroxyacetic acid, hydrogen peroxide), 5.2 (8)